

“KUBOTA” Powered Industrial diesel driven generator sets with **“NEWAGE”** Electrical Back Ends, ranging from 12.5 – 50 KW, 120/ 240 Volts, 1-phase, 60 HZ based on standard equipment plus the following options:

STANDARD EQUIPMENT

- 12 volt electric starter
- 12 volt battery charging alternator
- Automatic engine shutdown for low oil pressure/high temperature
- Fuel filter
- Fuel transfer pump
- Dry air cleanser
- High ambient radiator cooling
- Heavy duty steel frame
- Single bearing generator
- Brushless exciter
- Unit mounted solid state voltage regulator
- Mounted Muffler Battery, Rack & Cables
- AC/DC Panel with 2-Wire Start Automatic Starting Capability
- Sub-Base Tank, single wall (100-200 Gal.)
- Aluminum Sound Attenuating Weather Enclosure
- Main Line Breaker
- Racor Fuel Water Separator
- Oil Drain Valve
- Two Year / 2000 Hours Factory Warranty on Total Assembly



Power KW 60hz / 50hz	Model	Weight (LBS)	Engine Model	# of Cyl	Tank Capacity	Overall Dimensions L.W.H	LEAD TIME
12.5 /	SEP 12.5 E	1100	V1505	3	100 Gal.	83"X30"X50"	2 wks
15.0 / 12.5	SEP 15.0 E	1280	D1703	3	100 Gal.	83"X30"X50"	2 wks
17.0 /	SEP 17.5 E	1280	V2203	4	100 Gal.	83"X30"X50"	2 wks
21.0 / 17.5	SEP 21.0 E	1280	V2203BG	4	100 Gal.	83"X30"X50"	2 wks
25.0 / 20.0	SEP 25.0 E	1280	V2003-T	4	100 Gal.	83"X30"X50"	2 wks
30.0 / 24.0	SEP 30.0 E	2000	V3300N	4	200 Gal.	99"X36"X65"	2 wks
40.0 / 32.0	SEP 40.0 E	2000	V3600T	4	200 Gal.	99"X36"X65"	2 wks
50.0 / 40.0	SEP 50.0 E	2000	V3800DIT	4	200 Gal.	99"X36"X65"	2 wks

Dimensions and weight are approximate. Prices and lead time are subject to change by manufacturer without prior notification. Prices does not include inbound freight to final destination.